


ZF 60000 SERIES

# ZF 60000 NR2H

---

## Product details



### Description

- Design, manufacture and quality control standards comply with ISO 9001 and AQAP
- Marine transmission with reduction drive gearing and hydraulically actuated multi-disc clutch for engagement
- Low weight design for heavy duty fast ferry applications. Also suitable for other weight sensitive craft, e.g. high speed motor yachts.
- Compatible with all types of engines and water jet propulsion.
- Output shaft rotating in the opposite direction to that of the input shaft.
- Easy installation and fully works tested for guaranteed reliability

### Features

- Case hardened and precisely ground gear teeth for long life and smooth running
- Compact, space-saving design, complete with integral oil cooler, pump and full-flow filter
- Modular component design for fast and easy service and repair.
- Lightweight cast aluminum alloy housing resistant to sea water corrosion.
- Smooth and reliable clutch operation with hydraulically controlled clutch engagement and electrical actuation
- One power take off (PTO) drive with SAE connection, permanently connected and driven from the input shaft.
- Trailing pump to guarantee adequate transmission lubrication when the output shaft is rotated with the input shaft stationary.
- HW version: special "AntiFlex" mounting arrangement to prevent housing and component stress as a result of hull distortion and temperature changes.



## Ratings


| Ratios                                | Power Factor |         | Input Power Capacity |      |          |       |          |       | Max.<br>kW | Max.<br>hp | Max.<br>RPM |
|---------------------------------------|--------------|---------|----------------------|------|----------|-------|----------|-------|------------|------------|-------------|
|                                       | kW/RPM       | hp/RPM  | kW                   | hp   | kW       | hp    | kW       | hp    |            |            |             |
| Medium Duty - Diesel <sup>9</sup>     |              |         | 750 RPM              |      | 1000 RPM |       | 1200 RPM |       |            |            |             |
| 1.500, 2.125, 2.226, 2.741            | 9.1000       | 12.2033 | 6825                 | 9152 | 9100     | 12203 | 10920    | 14643 | 10920      | 14643      | 1350        |
| Continuous Duty - Diesel <sup>9</sup> |              |         | 750 RPM              |      | 900 RPM  |       | 1000 RPM |       |            |            |             |
| 1.500, 2.125, 2.226, 2.741            | 9.1000       | 12.2033 | 6825                 | 9152 | 8190     | 10983 | 9100     | 12203 | 9100       | 12203      | 1350        |

\* Special Order Ratio

Footnotes:

<sup>9</sup> Left and Right version available.


## Dimensions



| A               | B1    | B2          | H1    | H2                | L     | L1                 | L2    |
|-----------------|-------|-------------|-------|-------------------|-------|--------------------|-------|
| Millimeter (mm) |       |             |       |                   |       |                    |       |
| 665.0           | 750.0 | 590.0       | 600.0 | 819.0             | 715.0 | 1045.0             | 817.0 |
| Inch (in)       |       |             |       |                   |       |                    |       |
| 26.18           | 29.53 | 23.23       | 23.62 | 32.24             | 28.15 | 41.14              | 32.17 |
| Weight (kg)     |       | Weight (lb) |       | Amount of Oil (l) |       | Amount of Oil (qt) |       |
| 4650            |       | 10251       |       | 200.0             |       | 212.0              |       |

## Output flange dimensions

| A     |       | B     |       | C     |       | D    |      | Bolt Holes |              |      |
|-------|-------|-------|-------|-------|-------|------|------|------------|--------------|------|
|       |       |       |       |       |       |      |      | No.        | Diameter (E) |      |
| mm    | in    | mm    | in    | mm    | in    | mm   | in   |            | mm           | in   |
| 650.0 | 25.59 | 580.0 | 22.83 | 500.0 | 19.69 | 55.0 | 2.17 | 24         | 36.4         | 1.43 |



# GENERAL INFORMATION

---

## Duty Definitions

### Pleasure Duty

Highly intermittent operation with very large variations in engine speed and power.

|                                       |  |
|---------------------------------------|--|
| Average engine operating hours limit: | 500 hours/year<br>300 hours/year for mechanical gearboxes          |
| Typical hull forms:                   | Planing  |
| Applications:                         | Private, non-commercial, non-charter leisure activities, no racing |

### Light Duty

Intermittent operation with large variations in engine speed and power.

|                                       |   |
|---------------------------------------|---|
| Average engine operating hours limit: | 2500 hours/year<br>(for hydraulic transmissions smaller than ZF 2000 series, 2000 hours/year) |
| Typical hull forms:                   | Planing and semi-displacement   |
| Typical applications:                 | Private and charter, sport/leisure activities, naval and police activities                    |

### Medium Duty

Intermittent operation with some variations in engine speed and power.

|                                       |  |
|---------------------------------------|--|
| Average engine operating hours limit: | 4000 hours/year<br>(for hydraulic transmissions smaller than ZF 2000 series and workboat ZF W2700 series, 3500 hours/year) |
| Typical hull forms:                   | Semi-displacement and displacement   |
| Typical applications:                 | Charter and commercial craft (example: crew boats), and naval and police activities  |

### Continuous Duty

Continuous operation with little or no variations in engine speed and power.

|                                       |                               |
|---------------------------------------|-------------------------------|
| Average engine operating hours limit: | Unlimited                     |
| Typical hull forms:                   | Displacement                  |
| Typical applications:                 | Heavy duty commercial vessels |

---

## Technical Notes

### Duty Ratings

Ratings apply to marine diesel engines at the indicated speeds. At other engine speeds, the respective power capacity (kW) of the transmission can be obtained by multiplying the Power/Speed ratio by the speed. Approximate conversion factors:

- 1 kW = 1.36 metric hp
- 1 kW = 1.34 U.S. hp (SAE)
- 1 U.S. hp = 1.014 metric hp
- 1 Nm = 0.74 lb.ft.
- 1 Kg = 0.454 lb

Ratings apply to right hand turning engines, i.e. engines having counterclockwise rotating flywheels when viewing the flywheel end of the engine. These ratings allow full power through forward and reverse gear trains, unless otherwise stated. Contact your nearest ZF Sales and Service office for ratings applicable to gas turbines, as well as left hand turning engines, and marine transmissions for large horsepower capacity engines. Ratings apply to marine transmissions currently in production or in development and are subject to change without prior notice.

**NOTE:** The maximum rated input power must not be exceeded (see respective ratings in the technical data sheets).

### Safe Operating Notice

The safe operation of ZF products depends upon adherence to technical data presented in our brochures. Safe operation also depends upon proper installation, operation and routine maintenance and inspection under prevailing conditions and recommendations set forth by ZF. Damage to transmission caused by repeated or continuous emergency manoeuvres or abnormal operation is not covered under warranty. It is the responsibility of users and not ZF to provide and install guards and safety devices, which may be required by recognized safety standards of the respective country (e.g. for U.S.A. - the Occupational Safety Act of 1970 and its subsequent provisions).

### Monitoring Notice

The safe operation of ZF products depends upon adherence to ZF monitoring recommendations presented in our operating manuals, etc. It is the responsibility of users and not ZF to provide and install monitoring devices and safety interlock systems as may be deemed prudent by ZF. Consult ZF for details and recommendations.

### Survey Society Classification

In most cases, the maximum medium and continuous duty ratings permitted by ZF are accepted in full by major classification societies. If classification is required, contact ZF regarding proper procedures (also for yacht service and ice classifications service).

### Dimensions and Weights

Dimensions and weights refer to transmissions with bell housing (where appropriate) but excluding options such as: trolling valves, power take-offs, propeller shaft companion flanges, torsional couplings etc.

---

## Torsional Vibration and Torsional Couplings

The responsibility for ensuring torsional vibration compatibility rests with the overall propulsion system integration responsible party.

Compatibility check of torsional vibration must include excitations induced by engine governor. ZF cannot accept any liability for gearbox noise or for damage to the gearbox, the flexible coupling or to other parts of the drive unit caused by torsional vibrations. Contact ZF for further information and assistance.

For single engine powered boats, where loss of propulsion can result in loss of control, ZF recommends the use of a torsional limit stop. It is the buyer's responsibility to specify this option. ZF cannot accept any liability for personal injury, loss of life or damage or loss of property due to the failure of the buyer to specify a torsional limit stop.

ZF selects torsional couplings on the basis of nominal input torque at commonly rated engine speeds. Consult ZF for details concerning speed limits of standard offered torsional couplings, which can be below transmission limits. Special torsional couplings may be required for Survey Society requirements.